



PCN 1

ED-CM4SEN Release

EDA Technology Co., LTD

December 2023

Contact Us

Thank you very much for purchasing and using our products, and we will serve you wholeheartedly.

As one of the global design partners of Raspberry Pi, we are committed to providing hardware solutions for IOT, industrial control, automation, green energy and artificial intelligence based on Raspberry Pi technology platform.

You can contact us in the following ways:

EDA Technology Co.,LTD

Address:Room 301, Building 24, No.1661 Jialuo Road, Jiading District,
Shanghai

Mail: sales@edatec.cn

Phone: +86-18217351262

Website: <https://www.edatec.cn>

Technical Support:

Mail: support@edatec.cn

Phone: +86-18627838895

Wechat: zzw_1998-

Copyright Statement

EDA Technology Co.,LTD owns the copyright of this document and reserves all rights. Without the written permission of EDA Technology Co.,LTD, no part of this document may be modified, distributed or copied in any way or form.

Disclaimer

EDA Technology Co.,LTD does not guarantee that the information in this manual is up to date, correct, complete or of high quality. EDA Technology Co.,LTD also does not guarantee the further use of this information. If the material or non-material related losses are caused by using or not using the information in this manual, or by using incorrect or incomplete information, as long as it is not proved that it is the intention or negligence of EDA Technology Co.,LTD, the liability claim for EDA Technology Co.,LTD can be exempted. EDA Technology Co.,LTD expressly reserves the right to modify or supplement the contents or part of this manual without special notice.

Document version history

Release	Date	Description
1.0	8 th December 2023	Initial release

1 Product Change Note

- ✓ Notification date
- ✓ Products Affected
- ✓ New Product Version
- ✓ Reason for Change
- ✓ Change Description

1.1 Notification date

8th December 2023

1.2 Products Affected

ED-CM4SEN V1.2

1.3 New Product Version

ED-CM4SEN V1.2b

1.4 Reason for Change

Upgrade products to meet marketing requirement.

1.5 Change Description


1.5.1 New Function

NONE

1.5.2 Optimization

Changes	Results
Change the pull-up resistor and pull-down resistor of 4 RS485 circuits to 680Ω(The old version is 4.7kΩ).	<ul style="list-style-type: none">● It will provide better compatibility and driving capabilities of RS485.● Compatibles with long distance and high baud rate transmission of RS485 signal.● Supporting to connect more RS485 devices on RS485 bus.
Remove the 120Ω terminal resistors of 4 RS485 circuits.	

The detailed modifications are as shown below:



Except for the above changes, everything else keep the same.

A detailed test report will be provided at the end of December.